



Richpeace Quilting & Embroidery machine is perfectly controlled by computer system, easy to learn, easy to operate. This machine model merges the specific property of quilting machine and embroider machine. It is stable and continuously working without frame. 富怡绗缝机电脑控制，操作简单，易于学习，易于维护，可靠性强。集绗缝机、绣花机功能于一体，在绗缝的同时可以进行精致花型的绣做。

Production Variety

This machine is widely used for producing garments and all kinds of high-quality bedding products, such as, bed cover, bedspread, quilt, pillow cover, sleeping bag, etc.

绗缝机广泛应用于服装加工及各种床上用品，例如，床垫、床罩、被子、枕套、睡袋等。

绗绣加工产品

1. Hi-end embroidery machine heads are adopted to improve the accuracy of embroidery.
2. Automatic loosening system to flatten the fabric.
3. X-axis and Y-axis driven by Panasonic servo motors to ensure high speed quilting with high accuracy.
4. Automatic oiling system: apply the unique spray to lubricate the key parts, which extend service life of the machine.
5. Continuously quilting in Y direction: save the time of changing fabric and improve the quilting efficiency.
6. Automatic thread trimming function.
7. Go back quilting function.
8. Automatic thread breakage detection.
9. Power-off protection.
10. Japan KOBAN jumbo roxary hook.

Main Features

主要特色

1. 高档绣花机机头设计：提高绗绣精度
2. 自动松布系统：确保布料不变形
3. X/Y方向伺服电机驱动，确保高速绣做
4. 自动供油系统：独有的喷雾设计，使机头全方位润滑，延长机器使用寿命
5. Y向连续绗缝，节省换布时间，提高绗缝效率
6. 自动剪线功能
7. 自动退绣功能
8. 断线检测功能
9. 断电保护系统
10. 日本佐文大旋梭

Computer controlling system

电脑控制系统



10.4" LCD computer touch screen system allows you to easily finish all the operation just by touching the screen.
10.4 英寸液晶电脑触摸屏让您仅需点击屏幕即可完成绣做过程。

Roller system

罗拉装置



1. Rollers adopt technique of static equilibrium so that the machine will keep the proper position and the patterns will not be changed.
 2. Roller system enables mass production and continuously working as well.
1. 罗拉采用静平衡技术，确保罗拉在机器运作过程中或停机后位置准确，从而确保绗绣花样不变形。
2. 罗拉装置实现了高效持续绣做，节省人力和物力。

Auto-oiling System

自动润滑装置



1. Automatic lubrication system: apply the unique spray to lubricate the key parts, which extend service life of the machine
 2. Pneumatic system drives the sequin device to operate.
1. 自动润滑装置
独有的喷雾设备喷出油雾，大面积润滑零件，延长机器工作寿命。
2. 气动系统推动亮片装置运作

Options

选项装置



亮片装置、简易绳绣装置、跟踪绳绣装置
Sequin device Cording device Tracing cording device

Specifications

参数

机型 Model	RPQ-E-424-135 (270) -T-1
头数 Number of head	24
机头颜色 Needle of head	4色和6色可选 4 or 6 for option
绗绣面积 Quilting area(mm)	X向单个花型 135/270 X direction(single pattern) 135/270
全部面宽 Whole width 3240	
绗绣速度 Speed	最高速度：1000转/工作速度：800转 max.: 1000rpm working speed: 800rpm
针迹长度 Length of stitch	0.15-12.4mm
储存针数 Stitch storage	1300万 13million stitches
花样储存容量 Pattern Storage	200个花样 200 patterns
供电 Power Supply	三相 380V 50HZ Three-phase 380V 50HZ
功率 Power	4.5-5KW

